

■ Technical characteristics

Model Type	Nom. speed (r.p.m.)	Maximum absorbed power at 0Pa (W)	Maximum absorbed current (A)	Duty at free discharge (m³/h)	Maximum operating temperature (°C)	Sound pressure level* (dB(A))	Weight (kg)
TD-160/100N	2500	35	0,25	160	40	18	1,4
	2100	23	0,15	130	40	14	
TD-250/100	1880	39	0,26	250	40	28	2,0
	1475	26	0,18	185	40	23	
TD-350/125	2210	56	0,37	360	40	30	2,0
	1900	40	0,26	300	40	26	
TD-500/ ¹⁵⁰ ₁₆₀	2500	68	0,30	535	60	41	2,7
	1850	50	0,22	400	60	33	
TD-800/200N	2700	80	0,35	907	60	41	4,9
	2100	70	0,30	700	60	36	
TD-800/200	2450	128	0,55	880	60	45	4,9
	2040	96	0,41	665	60	37	
TD-1000/250	2800	155	0,65	1010	60	49	9,4
	2100	85	0,39	850	60	43	
TD-1300/250	2520	170	0,72	1300	60	49	9,4
	1990	110	0,48	950	60	44	
TD-2000/315	2760	350	1,30	1990	60	52	14,0
		200	0,90	1510	60	50	

* Radiated sound level measured at 3 m from product casing at free air conditions.